



**RED ENERGY SDN BHD (99405-H)**

No. 22, Jalan Anggerik Mokara 31/59,  
Seksyen 31, Kawasan Perindustrian Kota Kemuning, 40460  
Shah Alam, Selangor, Malaysia.

TEL : + 603 5122 8881, FAX : + 603 5122 9991

WEBSITE: [www.redenergy.com.my](http://www.redenergy.com.my)

E-MAIL: [admin@redenergy.com.my](mailto:admin@redenergy.com.my)

## RUBBER PRODUCTS



## RUBBER FOR PULLEY LAGGING

At drive pulleys, it's highly recommended to use diamond-groove profile to increase traction, minimize slippage and improve self-cleaning. This rubber comes with **special adhesive layer** to reduce chances of lagging peel-off.



Plain surface

Small diamond-  
groove surface

Large diamond-  
groove surface

*A = with adhesive layer  
B = without adhesive layer*

**Dimension [Thickness x Width x Length]**  
10 x 2,000 x 10,000 mm

*A lagging for all applications,  
with a well-balanced mix  
of strength, hardness and  
resistance to abrasion*

DIN 53516  
*Colour black, Elastomer SBR, IR  
Hardness 60±5 Shore A DIN 53505  
Rebound resilience 35% DIN 53512*



## RUBBER FOR SKIRT BOARD

Proven performance in slurry handling application such as pipelines, chutes and tank lining, hydrocyclones, sumps etc. Also use in wide range of sealing problem.



**Outstanding resilience & elasticity**

**Excellent sealing characteristic**

**Excellent shock, vibration and noise absorption properties**

### **Sizes**

Standard sheet size: 9.25m X 1.25 m; 1.5m X 10m

Standard thickness range : 2.0mm to 30mm ( approx. 1/16" to 1 1/4")

Moulded components available

DIN 53516, *Abrasion resistance 210mm<sup>3</sup>*

*Rebound Resilience 70% DIN53516*

*Hardness 45~60 IRHD*



## **COLD JOINT & PATCHING COMPOUND**

### **APPLICATION: COLD JOINT**

For conveyor belt cold-joining process, use TL-T-70 for stronger adhesion and faster drying time.



**TOPGUM TL-T 70**

*Complete set 1000 g solution + 70 g hardener*

### **APPLICATION: COLD PATCHING**

For conveyor belt cold-patching process, use RE Cold Repair Strip with bonding layer



on both sides.

*RE Patching Strip, 1.8mm (thickness) x 220mm x 10mtrs.*